

Features

- Low Standing Wave
- High Attenuation Accuracy
- High Indicator Stability
- Connector: SMA Male ↔ SMA Female
- Body Material: Stainless Steel 303F / Passivated
- Conductor Material: Beryllium Bronze / Gold Plated
- Durability: 500 cycles
- Average Power: 2W
- Impedance: 50 Ω
- Operating Temperature: -40 ~ +125 °C



Attenuation Value (dB)	Attenuation Accuracy (dB)	Frequency (GHz)	VSWR
1	±0.5	DC~18	≤1.30
3	±0.5	DC~18	≤1.30
6	±0.5	DC~18	≤1.30
10	±0.5	DC~18	≤1.30
20	±0.75	DC~18	≤1.30
30	±0.75	DC~18	≤1.30
40	±1.0	DC~18	≤1.30

N Type Fixed Attenuators

Features

- Low Standing Wave
- High Attenuation Accuracy
- High Indicator Stability
- Connector: N Male ↔ N Female
- Body Material: Stainless Steel 303F / Passivated
- Conductor Material: Beryllium Bronze / Gold Plated
- Durability: 500 cycles
- Average Power: 2W
- Impedance: 50 Ω
- Operating Temperature: -40 ~ +125 °C

Attenuation Value (dB)	Attenuation Accuracy (dB)	Frequency (GHz)	VSWR
1	±0.6	DC~18	≤1.35
3	±0.6	DC~18	≤1.35
6	±0.6	DC~18	≤1.35
10	±0.6	DC~18	≤1.35
20	±0.85	DC~18	≤1.35
30	±0.85	DC~18	≤1.35
40	±1.0	DC~18	≤1.35

3.5mm Fixed Attenuators

Features

- Low Standing Wave
- High Attenuation Accuracy
- High Indicator Stability
- Connector: 3.5mm Male ↔ 3.5mm Female
- Body Material: Stainless Steel 303F / Passivated
- Conductor Material: Beryllium Bronze / Gold Plated
- Durability: 500 cycles
- Average Power: 2W
- Impedance: 50 Ω
- Operating Temperature: -40 ~ +125 °C



Attenuation Value (dB)	Attenuation Accuracy (dB)	Frequency (GHz)	VSWR
1	±0.8	DC~26.5	≤1.35
3	±0.8	DC~26.5	≤1.35
6	±0.8	DC~26.5	≤1.35
10	±0.8	DC~26.5	≤1.35
20	±1.0	DC~26.5	≤1.35
30	±1.0	DC~26.5	≤1.35
40	±1.2	DC~26.5	≤1.35

2.92mm Fixed Attenuators

Features

- Low Standing Wave
- High Attenuation Accuracy
- High Indicator Stability
- Connector: 2.92mm Male ↔ 2.92mm Female
- Body Material: Stainless Steel 303F / Passivated
- Conductor Material: Beryllium Bronze / Gold Plated
- Durability: 500 cycles
- Average Power: 2W
- Impedance: 50 Ω
- Operating Temperature: -40 ~ +125 °C

Attenuation Value (dB)	Attenuation Accuracy (dB)	Frequency (GHz)	VSWR
1	±1.0	DC~40	≤1.30
3	±1.0	DC~40	≤1.30
6	±1.0	DC~40	≤1.30
10	±1.0	DC~40	≤1.30
20	±1.0	DC~40	≤1.30
30	±1.2	DC~40	≤1.30

2.4mm Fixed Attenuators

Features

- Low Standing Wave
- High Attenuation Accuracy
- High Indicator Stability
- Connector: 2.4mm Male ↔ 2.4mm Female
- Body Material: Stainless Steel 303F / Passivated
- Conductor Material: Beryllium Bronze / Gold Plated
- Durability: 500 cycles
- Average Power: 2W
- Impedance: 50 Ω
- Operating Temperature: -40 ~ +125 °C

Attenuation Value (dB)	Attenuation Accuracy (dB)	Frequency (GHz)	VSWR
1	±1.2	DC~50	≤1.40
3	±1.2	DC~50	≤1.40
6	±1.2	DC~50	≤1.40
10	±1.2	DC~50	≤1.40
20	±1.2	DC~50	≤1.40
30	±1.4	DC~50	≤1.40